

# GLOBAL EAST ASIA TECHNOLOGY CO.,LTD

www.global-antenna.com

## 800MHz Panel Antenna

GL-DY800V7



Electrical index	
Frequency Range-MHz	824-896
V.S.W.R	≤1.5
Gain-dBi	6.7
Horizontal Beam width-°	60
Vertical Beam width-°	50
F/B Ratio-dB	≥20dB
Polarization	Vertical
Input Impedance-Ω	50
Max Power-W	100
Lighting Protection	DC Ground
Mechanical Index	
Connector	N female
Installation	Wall mounting or rack mounting
Dimension	250×220×60mm
Weight	0.7kg

Tel: 86-0371-58561629

Email: [admin@global-antenna.com](mailto:admin@global-antenna.com)

Add: No 58,Rantun RD,Zhongyuan District,Zhengzhou,China

# GLOBAL EAST ASIA TECHNOLOGY CO.,LTD

www.global-antenna.com

Radiator Material	Aluminum
Radome material	ABS
Radome color	white
Work temperature-	-40°C to +65 °C
Pole Diameter-mm	φ 35 ~ φ 50

Tel: 86-0371-58561629

Email: [admin@global-antenna.com](mailto:admin@global-antenna.com)

Add: No 58,Rantun RD,Zhongyuan District,Zhengzhou,China