

GLGTDB10W 200-512 MHz Broadband Whip Antenna

MODEL GLGTDB10W

Broadband whip antenna covering 200-512 MHz with a TNC male connector.



KEY PERFORMANCE

200-512 MHz

FREQUENCY RANGE

0 dBi

GAIN

<= 2.5

VSWR

TNC male

CONNECTOR

TECHNICAL SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

Frequency range	200-512 MHz
Gain	0 dBi
Horizontal beamwidth	360°
Vertical beamwidth	53° ± 5°
VSWR	<= 2.5
Ovality	<= 2 dB
Impedance	50 ohm
Polarization	Vertical
Max. power	10 W
Connector	TNC male

MECHANICAL SPECIFICATIONS

Dimensions	250 mm / 330 mm
Weight	Approx. 78 g
Main material	Copper
Radome color	Black
Operational humidity	< 95%
Waterproof rating	IP65
Radome material	PE
Operating temperature	-40°C to +65°C

GLOBAL RF TECH

Zhengzhou LEHENG Electronic Technology Co., Ltd.
<https://globalrftech.com/> | Email Sales | Call Us

NEED A CUSTOM CONFIGURATION?

Frequency, connector, cable length and mounting options can be reviewed for your project.

[Request a quote](#)