

GLCKF2400V10 2400-2483 MHz 10 dBi Fiberglass Omni Antenna

MODEL GLCKF2400V10

2.4 GHz fiberglass omnidirectional antenna for WLAN and ISM systems.



KEY PERFORMANCE

2400-2483 MHz

FREQUENCY RANGE

10 dBi

PEAK GAIN

<= 1.5

VSWR

N Female

CONNECTOR

TECHNICAL SPECIFICATIONS

ELECTRICAL	
Frequency range	2400-2483 MHz
VSWR	<= 1.5
Gain	10 dBi
Horizontal beamwidth	360 deg
Vertical beamwidth	10 deg
Polarization	Vertical
Input impedance	50 ohm
Max. power	100 W
Lightning protection	DC grounded
MECHANICAL	
Connector type	N Female (N-K)
Antenna dimension	Dia. 20 x 850 mm
Weight	0.54 kg
Radome material	Fiberglass
Radome color	Grey
Operating temperature	-40 to +60 degC
Rated wind velocity	60 m/s
Mast diameter	Dia. 35-60 mm

GLOBAL RF TECH

Zhengzhou LEHENG Electronic Technology Co., Ltd.
<https://globalrftech.com/> | Email Sales | Call Us

NEED A CUSTOM CONFIGURATION?

Frequency, connector, cable length and mounting options can be reviewed for your project.

[Request a quote](#)