

GLTDTCS48 144/430 MHz 2.15/3.0 dBi Dual-Band Mobile Antenna

MODEL GLTDTCS48

Dual-band VHF/UHF mobile antenna for 144 and 430 MHz amateur and commercial radio with SMA or BNC connector.



KEY PERFORMANCE

144 / 430 MHz

FREQUENCY

2.15 / 3.0 dBi

GAIN

20 W

MAX. POWER

480 mm

LENGTH

TECHNICAL SPECIFICATIONS

ELECTRICAL	
Frequency	144 / 430 MHz
VSWR	< 1.5
Gain	2.15 / 3.0 dBi
Max. power	20 W
Impedance	50 ohm
Polarization	Vertical
Radiation pattern	Omni-directional
MECHANICAL	
Length	480 mm
Connector	SMA Female / SMA Male / BNC

NOTES

Source PDF is a single-page spec sheet. Product image is a 2-band whip antenna on white background; source SWR sweep also available as appendix if needed.

GLOBAL RF TECH

Zhengzhou LEHENG Electronic Technology Co., Ltd.
<https://globalrftech.com/> | Email Sales | Call Us

NEED A CUSTOM CONFIGURATION?

Frequency, connector, cable length and mounting options can be reviewed for your project.
[Request a quote](#)